



FULL FAMILY SPECIFICATIONS 2024

QUALITY BY DESIGN

Aerial Work Platforms

MODEL	MAX. PLATFORM HEIGHT		WIDTH		LIFT CAPACITY	
	US	METRIC	US	METRIC	US	METRIC
Aerial Work Platforms						
AWP®-20S	20 ft 1 in	6.12 m	2 ft 5 in	0.74 m	350 lb	159 kg
AWP-25S	24 ft 9 in	7.54 m	2 ft 5 in	0.74 m	350 lb	159 kg
AWP-30S	29 ft 6 in	9.00 m	2 ft 5 in	0.74 m	350 lb	159 kg
AWP-36S	36 ft 5 in	11.10 m	2 ft 5 in	0.74 m	350 lb	159 kg
AWP-40S	40 ft 3 in	12.30 m	2 ft 5 in	0.74 m	300 lb	136 kg
Self-Propelled Aerial Work Platforms (Genie® Runabout™ Family)						
GR™-12	11 ft 4 in	3.45 m	2 ft 5.5 in	0.75 m	500 lb	227 kg
GR-15	14 ft 8 in	4.47 m	2 ft 5.5 in	0.75 m	500 lb	227 kg
GR-20	19 ft 9 in	6.02 m	2 ft 7.5 in	0.80 m	350 lb	159 kg
Self-Propelled Aerial Work Platform with Jib (Genie Runabout Family)						
GR-26J	25 ft 11 in	7.90 m	3 ft 3 in	0.99 m	440 lb	200 kg

Material Lifts

MODEL	LIFTING HEIGHT		LIFTING CAPACITY	
	US	METRIC	US	METRIC
Super Hoist®				
GH™ 3.8	12 ft 5.6 in	3.80 m	350 lb	158 kg
GH 5.6*	18 ft 4.5 in	5.60 m	350 lb	158 kg
Genie® Lift™				
GL™-4	5 ft 11 in	1.80 m	500 lb	227 kg
GL-8	10 ft 0.5 in	3.06 m	400 lb	182 kg
GL-10	11 ft 8 in	3.56 m	350 lb	159 kg
GL-12	13 ft 9.5 in	4.20 m	350 lb	159 kg
Superlift Contractor®				
SLC™-12	12 ft 11 in	3.94 m	650 lb	295 kg
SLC-18	18 ft 6 in	5.64 m	650 lb	295 kg
SLC-24	24 ft	7.32 m	650 lb	295 kg
Superlift Advantage®				
SLA™-5	6 ft 7 in	2.00 m	1,000 lb	454 kg
SLA-10	11 ft 5.5 in	3.49 m	1,000 lb	454 kg
SLA-15	16 ft 4 in	4.98 m	800 lb	363 kg
SLA-20	21 ft 2.5 in	6.46 m	800 lb	363 kg
SLA-25	26 ft 0.5 in	7.94 m	650 lb	295 kg

Self-Propelled Scissor Lifts

MODEL	MAX. PLATFORM HEIGHT		WIDTH		LIFT CAPACITY	
	US	METRIC	US	METRIC	US	METRIC
Electric E-Drive Scissor Lifts						
GS™-1432m	14 ft 1 in	4.30 m	2 ft 8 in	0.81 m	500 lb	227 kg
GS-1932m	18 ft 3 in	5.55 m	2 ft 8 in	0.81 m	500 lb	227 kg
GS-1930	19 ft 3 in	5.85 m	2 ft 6.2 in	0.77 m	500 lb	227 kg
GS-1932	19 ft 3 in	5.85 m	2 ft 8.2 in	0.82 m	500 lb	227 kg
GS-2632	26 ft 1 in	7.96 m	2 ft 8.2 in	0.82 m	500 lb	227 kg
GS-3232	32 ft 1 in	9.78 m	2 ft 8.2 in	0.82 m	500 lb	227 kg
GS-2646	26 ft 1 in	7.96 m	3 ft 10 in	1.18 m	1,000 lb	454 kg
GS-3246	32 ft 1 in	9.78 m	3 ft 10 in	1.18 m	700 lb	318 kg
GS-4046	39 ft 2 in	11.94 m	3 ft 10 in	1.18 m	770 lb	350 kg
GS-4655	45 ft 9 in	13.95 m	4 ft 7 in	1.40 m	770 lb	350 kg
Rough Terrain Scissor Lifts						
GS-2669 RT/DC	26 ft 2 in	8.00 m	5 ft 9 in	1.75 m	1,500 lb	680 kg
GS-3369 RT/DC	32 ft 8 in	9.96 m	5 ft 9 in	1.75 m	1,000 lb	454 kg
GS-4069 RT/DC	40 ft 3 in	12.30 m	5 ft 9 in	1.75 m	800 lb	363 kg
GS-3390	33 ft	10.10 m	7 ft 8 in	2.34 m	2,500 lb	1,134 kg
GS-4390	43 ft	13.10 m	7 ft 8 in	2.34 m	1,500 lb	680 kg
GS-5390	53 ft	16.15 m	7 ft 8 in	2.34 m	1,500 lb	680 kg

Articulating Z®-Boom Lifts

MODEL	MAX. PLATFORM HEIGHT		WIDTH		HORIZONTAL REACH		UP & OVER CLEARANCE		LIFT CAPACITY	
	US	METRIC	US	METRIC	US	METRIC	US	METRIC	US	METRIC
Narrow Articulating Z-Boom Lifts										
Z-30/20N	30 ft	9.14 m	3 ft 11 in	1.19 m	21 ft 5 in	6.53 m	12 ft 8 in	3.86 m	500 lb	227 kg
Z-30/20N RJ	29 ft 2 in	8.89 m	3 ft 11 in	1.19 m	20 ft 6 in	6.25 m	12 ft 8 in	3.86 m	500 lb	227 kg
Z-34/22N	34 ft 6 in	10.52 m	4 ft 10 in	1.47 m	22 ft 3 in	6.78 m	15 ft 3 in	4.65 m	500 lb	227 kg
Z-40/23N	40 ft 5 in	12.32 m	4 ft 11 in	1.50 m	22 ft 8 in	6.91 m	21 ft 3 in	6.48 m	500 lb	227 kg
Z-40/23N RJ	40 ft 5 in	12.32 m	4 ft 11 in	1.50 m	22 ft 8 in	6.91 m	21 ft 3 in	6.48 m	500 lb	227 kg
Electric & Hybrid Articulating Z-Boom Lifts										
Z-34/22 DC	34 ft 6 in	10.52 m	5 ft 8 in	1.73 m	22 ft 3 in	6.78 m	15 ft	4.57 m	500 lb	227 kg
Z-45/25J DC	45 ft 9 in	13.94 m	5 ft 10.3 in	1.79 m	25 ft 1 in	7.65 m	23 ft 9 in	7.24 m	500 lb	227 kg
Z-45 DC & Z-45 FE	45 ft 8 in	13.92 m	7 ft 6 in	2.29 m	22 ft 9 in	6.94 m	24 ft 7 in	7.50 m	660 lb	300 kg
Z-60 DC & Z-60 FE	59 ft 7 in	18.16 m	8 ft 2 in	2.49 m	36 ft 7 in	11.15 m	24 ft 3 in	7.39 m	500 lb	227 kg
Engine-Powered Articulating Z-Boom Lifts										
Z-34/22 IC	34 ft 6 in	10.54 m	6 ft 1 in	1.85 m	22 ft 3 in	6.78 m	15 ft 1 in	4.60 m	500 lb	227 kg
Z-45 XC™	45 ft 6 in	13.86 m	7 ft 6 in	2.29 m	24 ft 9 in	7.55 m	24 ft 5 in	7.44 m	660/1,000 lb	300/454 kg
Z-45 HF	45 ft 6 in	13.86 m	8 ft 5 in	2.56 m	24 ft 9 in	7.55 m	24 ft 5 in	7.44 m	600 lb	272 kg
Z-62/40 & Z-62/40 TRAX	61 ft 11 in	18.87 m	8 ft 2 in	2.49 m	40 ft 9 in	12.42 m	25 ft 7 in	7.80 m	500 lb	227 kg
Z-90/60	78 ft	23.77 m	8 ft 2 in	2.49 m	60 ft	18.29 m	29 ft	8.83 m	500 lb	227 kg
ZX®-135/70	135 ft	41.15 m	8 ft 2 in*	2.49 m*	69 ft 9 in	21.26 m	75 ft 6 in	23.01 m	600 lb	272 kg

*Axles retracted

Telescopic S®-Boom Lifts

MODEL	MAX. PLATFORM HEIGHT		WIDTH		HORIZONTAL REACH		LIFT CAPACITY	
	US	METRIC	US	METRIC	US	METRIC	US	METRIC
J Series Telescopic S-Boom Lifts								
S-60 J	60 ft 10 in	18.50 m	8 ft 2 in	2.49 m	40 ft 6 in	12.3 m	660 lb	300 kg
S-80 J & S-80 J TRAX	80 ft 5 in	24.51 m	8 ft 2 in/8 ft 4 in	2.49 m/2.54 m	54 ft 9 in	16.69 m	660 lb	300 kg
Stick Telescopic S-Boom Lifts								
S-40 XC & S-40 TRAX	39 ft 6 in	12.04 m	8 ft 2 in/8 ft 1 in	2.49 m/2.46 m	31 ft 1 in	9.47 m	660/1,000 lb	300/454 kg
S-40 HF	39 ft 6 in	12.04 m	8 ft 5 in	2.56 m	28 ft 11 in	8.81 m	600 lb	272 kg
S-45 XC & S-45 TRAX	44 ft 6 in	13.56 m	8 ft 2 in/8 ft 1 in	2.49 m/2.46 m	36 ft 2 in	11.02 m	660/1,000 lb	300/454 kg
S-45 HF	44 ft 6 in	13.56 m	8 ft 5 in	2.56 m	34 ft	10.36 m	600 lb	272 kg
S-60 DC	61 ft 2 in	18.60 m	8 ft 2 in	2.49 m	40 ft 6 in	12.30 m	660 lb	300 kg
S-60 FE	61 ft 2 in	18.60 m	8 ft 2 in	2.49 m	40 ft 6 in	12.30 m	660 lb	300 kg
S-60 HF	60 ft 2 in	18.33 m	8 ft 5 in	2.56 m	46 ft 7 in	14.21 m	600/1,000 lb	272/454 kg
S-65 XC & S-65 TRAX	65 ft	19.81 m	8 ft 2 in/8 ft 6 in	2.49 m/2.58 m	54 ft 2 in	16.51 m	660/1,000 lb	300/454 kg
S-65 HF	65 ft 2 in	19.86 m	8 ft 5 in	2.56 m	51 ft 2 in	15.60 m	600/1,000 lb	272/454 kg
S-80 HF	80 ft	24.38 m	8 ft 6 in	2.59 m	68 ft 6 in	20.88 m	600/1,000 lb	272/454 kg
S-85 XC	85 ft	25.91 m	8 ft 2 in	2.49 m	74 ft 6 in	22.71 m	660/1,000 lb	300/454 kg
S-85 HF	85 ft	25.91 m	8 ft 6 in	2.59 m	72 ft 6 in	22.10 m	600/1,000 lb	272/454 kg
Super Telescopic S-Boom Lifts								
SX™-125 XC™	125 ft	38.10 m	8 ft 2 in*	2.49 m*	80 ft	24.38 m	660/1,000 lb	300/454 kg
SX-135 XC	135 ft	41.15 m	8 ft 2 in*	2.49 m*	90 ft	27.43 m	660/1,000 lb	300/454 kg
SX-150	152 ft	46.33 m	8 ft 2 in*	2.49 m*	80 ft	24.38 m	750 lb	340 kg
SX-180	180 ft	54.86 m	8 ft 2 in*	2.49 m*	80 ft	24.38 m	750 lb	340 kg

*Axles retracted

Telehandlers

MODEL	MAX. LIFT HEIGHT		MAX. FORWARD REACH		MAX. LIFT CAPACITY		CAPACITY AT MAX. HEIGHT		CAPACITY AT MAX. REACH	
	US	METRIC	US	METRIC	US	METRIC	US	METRIC	US	METRIC
Genie® Telehandlers										
GTH™-5519	18 ft 10 in	5.74 m	11 ft 3 in	3.43 m	5,500 lb	2,495 kg	4,400 lb	1,996 kg	1,900 lb	862 kg
GTH-636	36 ft	10.97 m	21 ft 11 in	6.68 m	6,000 lb	2,722 kg	5,000 lb	2,268 kg	1,500 lb	680 kg
GTH-844	43 ft 10 in	13.36 m	28 ft 2 in	8.59 m	8,000 lb	3,629 kg	6,000 lb	2,722 kg	2,000 lb	907 kg
GTH-1056	56 ft 7 in	17.25 m	42 ft	12.80 m	10,000 lb	4,536 kg	5,000 lb	2,268 kg	3,000 lb	1,361 kg
GTH-1256	56 ft 3 in	17.15 m	42 ft	12.80 m	12,000 lb	5,443 kg	6,000 lb	2,722 kg	3,500 lb	1,588 kg