



FULL FAMILY SPECIFICATIONS 2024



Material Lifts

MODEL	LIFTING HEIGHT		LIFTING CAPACITY	
	US	METRIC	US	METRIC
Super Hoist®				
GH™ 3.8	12 ft 5.6 in	3.80 m	350 lb	158 kg
GH 5.6*	18 ft 4.5 in	5.60 m	350 lb	158 kg
Genie® Lift™				
GL™-4	5 ft 11 in	1.80 m	500 lb	227 kg
GL-8	10 ft 0.5 in	3.06 m	400 lb	182 kg
GL-10	11 ft 8 in	3.56 m	350 lb	159 kg
GL-12	13 ft 9.5 in	4.20 m	350 lb	159 kg
Superlift Contractor®				
SLC™-12	12 ft 11 in	3.94 m	650 lb	295 kg
SLC-18	18 ft 6 in	5.64 m	650 lb	295 kg
SLC-24	24 ft	7.32 m	650 lb	295 kg
Superlift Advantage®				
SLA™-5	6 ft 7 in	2.00 m	1,000 lb	454 kg
SLA-10	11 ft 5.5 in	3.49 m	1,000 lb	454 kg
SLA-15	16 ft 4 in	4.98 m	800 lb	363 kg
SLA-20	21 ft 2.5 in	6.46 m	800 lb	363 kg
SLA-25	26 ft 0.5 in	7.94 m	650 lb	295 kg

Self-Propelled Scissor Lifts

MODEL	MAX. WORKING HEIGHT		WIDTH		LIFT CAPACITY	
	US	METRIC	US	METRIC	US	METRIC
Electric E-Drive Scissor Lifts						
GS™-1432m	20 ft 1 in	6.30 m	2 ft 8 in	0.81 m	500 lb	227 kg
GS-1932m	24 ft 3 in	7.55 m	2 ft 8 in	0.81 m	500 lb	227 kg
GS-1930	25 ft 3 in	7.85 m	2 ft 6.2 in	0.77 m	500 lb	227 kg
GS-1932	25 ft 3 in	7.85 m	2 ft 8.2 in	0.82 m	500 lb	227 kg
GS-2632	32 ft 1 in	9.96 m	2 ft 8.2 in	0.82 m	500 lb	227 kg
GS-3232	38 ft 1 in	11.78 m	2 ft 8.2 in	0.82 m	500 lb	227 kg
GS-2646	32 ft 1 in	9.96 m	3 ft 10 in	1.18 m	1,000 lb	454 kg
GS-3246	38 ft 1 in	11.78 m	3 ft 10 in	1.18 m	700 lb	318 kg
GS-4046	45 ft 2 in	13.94 m	3 ft 10 in	1.18 m	770 lb	350 kg
GS-4655	51 ft 9 in	15.95 m	4 ft 7 in	1.40 m	770 lb	350 kg
Rough Terrain Scissor Lifts						
GS-2669 RT/DC	32 ft 2 in	10.00 m	5 ft 9 in	1.75 m	1,500 lb	680 kg
GS-3369 RT/DC	38 ft 8 in	11.96 m	5 ft 9 in	1.75 m	1,000 lb	454 kg
GS-4069 RT/DC	46 ft 3 in	14.30 m	5 ft 9 in	1.75 m	800 lb	363 kg
GS-3390	39 ft	12.10 m	7 ft 8 in	2.34 m	2,500 lb	1,134 kg
GS-4390	49 ft	15.10 m	7 ft 8 in	2.34 m	1,500 lb	680 kg
GS-5390	59 ft	18.15 m	7 ft 8 in	2.34 m	1,500 lb	680 kg

Articulating Z®-Boom Lifts

MODEL	MAX. WORKING HEIGHT		WIDTH		HORIZONTAL REACH		UP & OVER CLEARANCE		LIFT CAPACITY	
	US	METRIC	US	METRIC	US	METRIC	US	METRIC	US	METRIC
Narrow Articulating Z-Boom Lifts										
Z-30/20N	36 ft	11.14 m	3 ft 11 in	1.19 m	21 ft 5 in	6.53 m	12 ft 8 in	3.86 m	500 lb	227 kg
Z-30/20N RJ	35 ft 2 in	10.89 m	3 ft 11 in	1.19 m	20 ft 6 in	6.25 m	12 ft 8 in	3.86 m	500 lb	227 kg
Z-34/22N	40 ft 6 in	12.52 m	4 ft 10 in	1.47 m	22 ft 3 in	6.78 m	15 ft 3 in	4.65 m	500 lb	227 kg
Electric & Hybrid Articulating Z-Boom Lifts										
Z-45/25J DC & BI-Energy	51 ft 9 in	15.94 m	5 ft 10.3 in	1.79 m	25 ft 1 in	7.65 m	23 ft 9 in	7.24 m	500 lb	227 kg
Z-45 DC & Z-45 FE	51 ft 8 in	15.92 m	7 ft 6 in	2.29 m	22 ft 9 in	6.94 m	24 ft 7 in	7.50 m	660 lb	300 kg
Z-60 DC & Z-60 FE	65 ft 7 in	20.16 m	8 ft 2 in	2.49 m	36 ft 7 in	11.15 m	24 ft 3 in	7.39 m	500 lb	227 kg
Engine-Powered Articulating Z-Boom Lifts										
Z-34/22 IC	40 ft 7 in	12.54 m	6 ft 1 in	1.85 m	22 ft 3 in	6.78 m	15 ft 1 in	4.60 m	500 lb	227 kg
Z-45/25J RT	51 ft 6 in	15.86 m	7 ft 6 in	2.29 m	24 ft 8 in	7.52 m	23 ft 7 in	7.14 m	500 lb	227 kg
Z-45 XC™	51 ft 6 in	15.86 m	7 ft 6 in	2.29 m	24 ft 9 in	7.55 m	24 ft 5 in	7.44 m	660/1,000 lb	300/454 kg
Z-51/30J RT	57 ft 8 in	17.59 m	7 ft 6 in	2.29 m	30 ft 9 in	9.37 m	24 ft 3 in	7.39 m	500 lb	227 kg
Z-62/40 & Z-62/40 TRAX	67 ft 11 in	20.87 m	8 ft 2 in	2.49 m	40 ft 9 in	12.42 m	25 ft 7 in	7.80 m	500 lb	227 kg
Z-80/60	84 ft	25.77 m	8 ft 2 in	2.49 m	60 ft	18.29 m	29 ft	8.83 m	500 lb	227 kg
ZX™-135/70	141 ft	43.15 m	8 ft 2 in*	2.49 m*	69 ft 9 in	21.26 m	75 ft 6 in	23.01 m	600 lb	272 kg

*Axles retracted

Aerial Work Platforms

MODEL	MAX. WORKING HEIGHT		WIDTH		LIFT CAPACITY	
	US	METRIC	US	METRIC	US	METRIC
Aerial Work Platforms						
AWP®-20S	26 ft 1 in	8.12 m	2 ft 5 in	0.74 m	350 lb	159 kg
AWP-25S	30 ft 9 in	9.54 m	0.74 m	0.74 m	350 lb	159 kg
AWP-30S	35 ft 6 in	11.00 m	2 ft 5 in	0.74 m	350 lb	159 kg
AWP-36S	42 ft 5 in	13.10 m	2 ft 5 in	0.74 m	350 lb	159 kg
AWP-40S	46 ft 3 in	14.30 m	2 ft 5 in	0.74 m	300 lb	136 kg
Self-Propelled Aerial Work Platforms (Genie® Runabout™ Family)						
GR™-12	17 ft 4 in	5.45 m	2 ft 5.5 in	0.75 m	500 lb	227 kg
GR-15	20 ft 8 in	6.47 m	2 ft 5.5 in	0.75 m	500 lb	227 kg
GR-20	25 ft 9 in	8.02 m	2 ft 7.5 in	0.80 m	350 lb	159 kg
Self-Propelled Aerial Work Platform with Jib (Genie Runabout Family)						
GR-20J	24 ft 8 in	7.70 m	3 ft 3 in	0.99 m	440 lb	200 kg
GR-26J	31 ft 11 in	9.90 m	3 ft 3 in	0.99 m	440 lb	200 kg

Telescopic S®-Boom Lifts

MODEL	MAX. WORKING HEIGHT		WIDTH		HORIZONTAL REACH		LIFT CAPACITY	
	US	METRIC	US	METRIC	US	METRIC	US	METRIC
J Series Telescopic S-Boom Lifts								
S-60 J	66 ft 10 in	20.50 m	8 ft 2 in	2.49 m	40 ft 6 in	12.3 m	660 lb	300 kg
S-80 J & S-80 J TRAX	86 ft 5 in	26.51 m	8 ft 2 in/8 ft 4 in	2.49 m/2.54 m	54 ft 9 in	16.69 m	660 lb	300 kg
Stick Telescopic S-Boom Lifts								
S-45 XC & S-45 TRAX	50 ft 6 in	15.56 m	8 ft 2 in/8 ft 1 in	2.49 m/2.46 m	36 ft 2 in	11.02 m	660/1,000 lb	300/454 kg
S-60 DC	67 ft 2 in	20.60 m	8 ft 2 in	2.49 m	40 ft 6 in	12.30 m	660 lb	300 kg
S-60 FE	67 ft 2 in	20.60 m	8 ft 2 in	2.49 m	40 ft 6 in	12.30 m	660 lb	300 kg
S-65 XC & S-65 TRAX	71 ft	21.81 m	8 ft 2 in/8 ft 6 in	2.49 m/2.58 m	54 ft 2 in	16.51 m	660/1,000 lb	300/454 kg
S-85 XC	91 ft	27.91 m	8 ft 2 in	2.49 m	74 ft 6 in	22.71 m	660/1,000 lb	300/454 kg
Super Telescopic S-Boom Lifts								
SX™-105 XC™	111 ft	34 m	8 ft 2 in*	2.49 m*	80 ft	24.38 m	660/1,000 lb	300/454 kg
SX-125 XC	131 ft	40.10 m	8 ft 2 in*	2.49 m*	80 ft	24.38 m	660/1,000 lb	300/454 kg
SX-135 XC	141 ft	43.15 m	8 ft 2 in*	2.49 m*	90 ft	27.43 m	660/1,000 lb	300/454 kg
SX-150	158 ft	48.33 m	8 ft 2 in*	2.49 m*	80 ft	24.38 m	750 lb	340 kg
SX-180	186 ft	56.86 m	8 ft 2 in*	2.49 m*	80 ft	24.38 m	750 lb	340 kg

*Axles retracted