



FULL FAMILY SPECIFICATIONS 2024



Material Lifts

| MODEL | LIFTING HEIGHT | | LIFTING CAPACITY | |
|------------------------------|----------------|--------|------------------|--------|
| | US | METRIC | US | METRIC |
| Super Hoist® | | | | |
| GH™ 3.8 | 12 ft 5.6 in | 3.80 m | 350 lb | 158 kg |
| GH 5.6* | 18 ft 4.5 in | 5.60 m | 350 lb | 158 kg |
| Genie® Lift™ | | | | |
| GL™-4 | 5 ft 11 in | 1.80 m | 500 lb | 227 kg |
| GL-8 | 10 ft 0.5 in | 3.06 m | 400 lb | 182 kg |
| GL-10 | 11 ft 8 in | 3.56 m | 350 lb | 159 kg |
| GL-12 | 13 ft 9.5 in | 4.20 m | 350 lb | 159 kg |
| Superlift Contractor® | | | | |
| SLC™-12 | 12 ft 11 in | 3.94 m | 650 lb | 295 kg |
| SLC-18 | 18 ft 6 in | 5.64 m | 650 lb | 295 kg |
| SLC-24 | 24 ft | 7.32 m | 650 lb | 295 kg |
| Superlift Advantage® | | | | |
| SLA™-5 | 6 ft 7 in | 2.00 m | 1,000 lb | 454 kg |
| SLA-10 | 11 ft 5.5 in | 3.49 m | 1,000 lb | 454 kg |
| SLA-15 | 16 ft 4 in | 4.98 m | 800 lb | 363 kg |
| SLA-20 | 21 ft 2.5 in | 6.46 m | 800 lb | 363 kg |
| SLA-25 | 26 ft 0.5 in | 7.94 m | 650 lb | 295 kg |

Self-Propelled Scissor Lifts

| MODEL | MAX. WORKING HEIGHT | | WIDTH | | LIFT CAPACITY | |
|---------------------------------------|---------------------|---------|-------------|--------|---------------|----------|
| | US | METRIC | US | METRIC | US | METRIC |
| Electric E-Drive Scissor Lifts | | | | | | |
| GS™-1432m | 20 ft 1 in | 6.30 m | 2 ft 8 in | 0.81 m | 500 lb | 227 kg |
| GS-1932m | 24 ft 3 in | 7.55 m | 2 ft 8 in | 0.81 m | 500 lb | 227 kg |
| GS-1930 | 25 ft 3 in | 7.85 m | 2 ft 6.2 in | 0.77 m | 500 lb | 227 kg |
| GS-1932 | 25 ft 3 in | 7.85 m | 2 ft 8.2 in | 0.82 m | 500 lb | 227 kg |
| GS-2632 | 32 ft 1 in | 9.96 m | 2 ft 8.2 in | 0.82 m | 500 lb | 227 kg |
| GS-3232 | 38 ft 1 in | 11.78 m | 2 ft 8.2 in | 0.82 m | 500 lb | 227 kg |
| GS-2646 | 32 ft 1 in | 9.96 m | 3 ft 10 in | 1.18 m | 1,000 lb | 454 kg |
| GS-3246 | 38 ft 1 in | 11.78 m | 3 ft 10 in | 1.18 m | 700 lb | 318 kg |
| GS-4046 | 45 ft 2 in | 13.94 m | 3 ft 10 in | 1.18 m | 770 lb | 350 kg |
| GS-4655 | 51 ft 9 in | 15.95 m | 4 ft 7 in | 1.40 m | 770 lb | 350 kg |
| Rough Terrain Scissor Lifts | | | | | | |
| GS-2669 RT/DC | 32 ft 2 in | 10.00 m | 5 ft 9 in | 1.75 m | 1,500 lb | 680 kg |
| GS-3369 RT/DC | 38 ft 8 in | 11.96 m | 5 ft 9 in | 1.75 m | 1,000 lb | 454 kg |
| GS-4069 RT/DC | 46 ft 3 in | 14.30 m | 5 ft 9 in | 1.75 m | 800 lb | 363 kg |
| GS-3390 | 39 ft | 12.10 m | 7 ft 8 in | 2.34 m | 2,500 lb | 1,134 kg |
| GS-4390 | 49 ft | 15.10 m | 7 ft 8 in | 2.34 m | 1,500 lb | 680 kg |
| GS-5390 | 59 ft | 18.15 m | 7 ft 8 in | 2.34 m | 1,500 lb | 680 kg |

Articulating Z-Boom Lifts

| MODEL | MAX. WORKING HEIGHT | | WIDTH | | HORIZONTAL REACH | | UP & OVER CLEARANCE | | LIFT CAPACITY | |
|--|---------------------|---------|--------------|---------|------------------|---------|---------------------|---------|---------------|------------|
| | US | METRIC | US | METRIC | US | METRIC | US | METRIC | US | METRIC |
| Narrow Articulating Z-Boom Lifts | | | | | | | | | | |
| Z-30/20N | 36 ft | 11.14 m | 3 ft 11 in | 1.19 m | 21 ft 5 in | 6.53 m | 12 ft 8 in | 3.86 m | 500 lb | 227 kg |
| Z-30/20N RJ | 35 ft 2 in | 10.89 m | 3 ft 11 in | 1.19 m | 20 ft 6 in | 6.25 m | 12 ft 8 in | 3.86 m | 500 lb | 227 kg |
| Z-34/22N | 40 ft 6 in | 12.52 m | 4 ft 10 in | 1.47 m | 22 ft 3 in | 6.78 m | 15 ft 3 in | 4.65 m | 500 lb | 227 kg |
| Electric & Hybrid Articulating Z-Boom Lifts | | | | | | | | | | |
| Z-45/25J DC & BI-Energy | 51 ft 9 in | 15.94 m | 5 ft 10.3 in | 1.79 m | 25 ft 1 in | 7.65 m | 23 ft 9 in | 7.24 m | 500 lb | 227 kg |
| Z-45 DC & Z-45 FE | 51 ft 8 in | 15.92 m | 7 ft 6 in | 2.29 m | 22 ft 9 in | 6.94 m | 24 ft 7 in | 7.50 m | 660 lb | 300 kg |
| Z-60 DC & Z-60 FE | 65 ft 7 in | 20.16 m | 8 ft 2 in | 2.49 m | 36 ft 7 in | 11.15 m | 24 ft 3 in | 7.39 m | 500 lb | 227 kg |
| Engine-Powered Articulating Z-Boom Lifts | | | | | | | | | | |
| Z-34/22 IC | 40 ft 7 in | 12.54 m | 6 ft 1 in | 1.85 m | 22 ft 3 in | 6.78 m | 15 ft 1 in | 4.60 m | 500 lb | 227 kg |
| Z-45/25J RT | 51 ft 6 in | 15.86 m | 7 ft 6 in | 2.29 m | 24 ft 8 in | 7.52 m | 23 ft 7 in | 7.14 m | 500 lb | 227 kg |
| Z-45 XC™ | 51 ft 6 in | 15.86 m | 7 ft 6 in | 2.29 m | 24 ft 9 in | 7.55 m | 24 ft 5 in | 7.44 m | 660/1,000 lb | 300/454 kg |
| Z-51/30J RT | 57 ft 8 in | 17.59 m | 7 ft 6 in | 2.29 m | 30 ft 9 in | 9.37 m | 24 ft 3 in | 7.39 m | 500 lb | 227 kg |
| Z-62/40 & Z-62/40 TRAX | 67 ft 11 in | 20.87 m | 8 ft 2 in | 2.49 m | 40 ft 9 in | 12.42 m | 25 ft 7 in | 7.80 m | 500 lb | 227 kg |
| Z-80/60 | 84 ft | 25.77 m | 8 ft 2 in | 2.49 m | 60 ft | 18.29 m | 29 ft | 8.83 m | 500 lb | 227 kg |
| ZX™-135/70 | 141 ft | 43.15 m | 8 ft 2 in* | 2.49 m* | 69 ft 9 in | 21.26 m | 75 ft 6 in | 23.01 m | 600 lb | 272 kg |

*Axles retracted

Aerial Work Platforms

| MODEL | MAX. WORKING HEIGHT | | WIDTH | | LIFT CAPACITY | |
|---|---------------------|---------|-------------|--------|---------------|--------|
| | US | METRIC | US | METRIC | US | METRIC |
| Aerial Work Platforms | | | | | | |
| AWP®-20S | 26 ft 1 in | 8.12 m | 2 ft 5 in | 0.74 m | 350 lb | 159 kg |
| AWP-25S | 30 ft 9 in | 9.54 m | 2 ft 5 in | 0.74 m | 350 lb | 159 kg |
| AWP-30S | 35 ft 6 in | 11.00 m | 2 ft 5 in | 0.74 m | 350 lb | 159 kg |
| AWP-36S | 42 ft 5 in | 13.10 m | 2 ft 5 in | 0.74 m | 350 lb | 159 kg |
| AWP-40S | 46 ft 3 in | 14.30 m | 2 ft 5 in | 0.74 m | 300 lb | 136 kg |
| Self-Propelled Aerial Work Platforms (Genie® Runabout™ Family) | | | | | | |
| GR™-12 | 17 ft 4 in | 5.45 m | 2 ft 5.5 in | 0.75 m | 500 lb | 227 kg |
| GR-15 | 20 ft 8 in | 6.47 m | 2 ft 5.5 in | 0.75 m | 500 lb | 227 kg |
| GR-20 | 25 ft 9 in | 8.02 m | 2 ft 7.5 in | 0.80 m | 350 lb | 159 kg |
| Self-Propelled Aerial Work Platform with Jib (Genie Runabout Family) | | | | | | |
| GR-20J | 24 ft 8 in | 7.70 m | 3 ft 3 in | 0.99 m | 440 lb | 200 kg |
| GR-26J | 31 ft 11 in | 9.90 m | 3 ft 3 in | 0.99 m | 440 lb | 200 kg |

Telescopic S-Boom Lifts

| MODEL | MAX. WORKING HEIGHT | | WIDTH | | HORIZONTAL REACH | | LIFT CAPACITY | |
|---|---------------------|---------|---------------------|---------------|------------------|---------|---------------|------------|
| | US | METRIC | US | METRIC | US | METRIC | US | METRIC |
| J Series Telescopic S-Boom Lifts | | | | | | | | |
| S-60 J | 66 ft 10 in | 20.50 m | 8 ft 2 in | 2.49 m | 40 ft 6 in | 12.3 m | 660 lb | 300 kg |
| S-80 J & S-80 J TRAX | 86 ft 5 in | 26.51 m | 8 ft 2 in/8 ft 4 in | 2.49 m/2.54 m | 54 ft 9 in | 16.69 m | 660 lb | 300 kg |
| Stick Telescopic S-Boom Lifts | | | | | | | | |
| S-45 XC & S-45 TRAX | 50 ft 6 in | 15.56 m | 8 ft 2 in/8 ft 1 in | 2.49 m/2.46 m | 36 ft 2 in | 11.02 m | 660/1,000 lb | 300/454 kg |
| S-60 DC | 67 ft 2 in | 20.60 m | 8 ft 2 in | 2.49 m | 40 ft 6 in | 12.30 m | 660 lb | 300 kg |
| S-60 FE | 67 ft 2 in | 20.60 m | 8 ft 2 in | 2.49 m | 40 ft 6 in | 12.30 m | 660 lb | 300 kg |
| S-65 XC & S-65 TRAX | 71 ft | 21.81 m | 8 ft 2 in/8 ft 6 in | 2.49 m/2.58 m | 54 ft 2 in | 16.51 m | 660/1,000 lb | 300/454 kg |
| S-85 XC | 91 ft | 27.91 m | 8 ft 2 in | 2.49 m | 74 ft 6 in | 22.71 m | 660/1,000 lb | 300/454 kg |
| Super Telescopic S-Boom Lifts | | | | | | | | |
| SX™-105 XC™ | 111 ft | 34 m | 8 ft 2 in* | 2.49 m* | 80 ft | 24.38 m | 660/1,000 lb | 300/454 kg |
| SX-125 XC | 131 ft | 40.10 m | 8 ft 2 in* | 2.49 m* | 80 ft | 24.38 m | 660/1,000 lb | 300/454 kg |
| SX-135 XC | 141 ft | 43.15 m | 8 ft 2 in* | 2.49 m* | 90 ft | 27.43 m | 660/1,000 lb | 300/454 kg |
| SX-150 | 158 ft | 48.33 m | 8 ft 2 in* | 2.49 m* | 80 ft | 24.38 m | 750 lb | 340 kg |
| SX-180 | 186 ft | 56.86 m | 8 ft 2 in* | 2.49 m* | 80 ft | 24.38 m | 750 lb | 340 kg |

*Axles retracted